



Gorilla Blue Hot PVC Glue™



Gorilla Blue Hot PVC Glue is great for pool, and turf/landscaping applications. This medium bodied, fast-setting cement is for use on PVC pipe and fittings up to 4" in diameter (schedule 80) and 6" in diameter (schedule 40), in wet conditions or where quick pressurization is desired.

Gorilla Blue Hot PVC Glue is the fastest acting cement we make. It sets fast so you can enjoy quick finished joints and pipe pressurization, even in the wettest of conditions.

With **Gorilla Blue Hot PVC Glue**, primer is not required on pipes below 4" (reference local codes to see where primer is required). Its consistent viscosity provides excellent gap-gilling capabilities and makes it easy to use. It meets all LOW-VOC requirements, as outlined by SCAQMD 1168/316A. And of course, it has Gorilla quality.

Manufactured to ASTM D 2564 standards, use it on piping systems for potable water, DWV (drain, waste, vent), electrical conduit, ENT, irrigation, well casing and sewer/drain applications.

Available in 4 oz. (#04102), 8 oz. (#08102), 16 oz. (#16102), quart (#32102) and gallon (#38102) sizes.

Gorilla Blue Hot PVC Glue...The Toughest PVC Cement On Planet Earth™.

TECHNICAL DATA

<u>PRODUCT</u>	<u>BODY</u>	<u>COLOR</u>	<u>DENSITY</u>	<u>SET TIME</u>
102	Medium	Blue	7.6 lb/gal	Very Fast

MAX VOC PER SCAQMD 1168/316A:	510 G/L
SPECIFICATIONS:	ASTM D 2564, SCAQMD 1168/316A
HYDROSTATIC PRESSURE TEST:	400 psi min. (73° F, 2 hour cure)
FLASH POINT:	-4° F (closed cup)
SHELF LIFE:	3 year minimum
LISTINGS:	NSF, UPC



Gorilla PVC Cement LLC • P.O. Box 848969, Hollywood, FL 33084

888-367-4583 • 866-782-4583 fax • www.GorillaPVC.com

To place an order email ann@gorillapvc.com